

MULTI-TOOL SYSTEM



Shindaiwa's Multi-Tool System is built for those looking for maximum versatility from a single power source that can be used with multiple attachments, plus a 3 ft. extension ensuring you have the right tool to accomplish the task at hand. The multi-tool system is a great alternative to dedicated units by reducing maintenance and space.



Engine CC	21.2
Weight (lbs)	9.8
Shaft Length (in.)	40.7
Fuel Capacity (fl. oz.)..	14.2



M235

The best choice for many residential yard chores.

- Tool-less coupler allows for fast, easy changes on multiple attachments
- Adjustable left handed grip for desired operator's hand position
- Vibration reduction system for increased comfort
- Accepts up to 9 Multi-Tool attachments



Engine CC	25.4
Weight (lbs)	10
Shaft Length (in.)	40.7
Fuel Capacity (fl. oz.)..	20.6



M262

More power for commercial applications.

- Tool-less coupler allows for fast, easy changes on up to 10 attachments
- Tool-less access, two-stage air filtration system dramatically increases ease of maintenance
- Engine vibration reducing mounting absorbs engine vibration
- Cushioned front and rear handles increases operator comfort

MULTI-TOOL SYSTEM ATTACHMENTS

These attachments only work with the M235 and M262 power sources.



Trimmer Attachment

Commercial-grade trimmer attachment using Shindaiwa's Speed-Feed® 400 head. 34 in. length, 3.2 lbs.

Part # 66001



Mid-Reach Articulated Hedge Trimmer

10-position articulation with a shorter shaft for maneuvering in tight areas. 38 in. length, 4.5 lbs.

Part # 66005



Tiller/Cultivator Attachment

6.5 in. swath and 42:1 gear reduction makes quick work of flower and garden bed maintenance. 35.7 in. length, 5.2 lbs.

Part # 66008



Lawn Edger Attachment

7.75 in. blade with open-face shield and guide for effortless edging. 30.8 in. length, 4.6 lbs.


Part # 66010



Brushcutter Attachment

Commercial-grade construction with 3-tooth grass and weed blade. 32.7 in. length, 2.6 lbs.

Part # 66004



PowerBroom™ Attachment

Ideal for cleaning gravel, mulch, or other debris from grass or artificial turf. 36.5 in. length, 11.3 lbs. Not compatible with the M235.

Part # 66011



Standard Hedge Trimmer

21 in. double-sided, double-reciprocating blades and an extra heavy-duty, professional-grade gear case. 50.1 in. length, 4.1 lbs.

Part # 66006



Pole Pruner Attachment

10 in. bar with long shaft for reaching high limbs. 57.1 in. length, 4.9 lbs.

Part # 66002



Articulated Hedge Trimmer

10-position articulation coupled with 21 in. blades and a 28 in. shaft for maximum reach. 64.4 in. length, 5.6 lbs.

Part # 66003



3 ft. Extension

Tool-less coupler allows easy installation between power source and attachments. Only for use with pole pruner and all hedge trimmer attachments. 39.2 in. length, 2.7 lbs.

Part # 66012

POLE PRUNER ATTACHMENT REPLACEMENT CHART

Bar Length (in.)	Fits	Replacement Bar	Replacement Chain
10	66002	S10A0CD3739	S91VXL39CQ

PRODUCT SPECIFICATIONS

CHAINSAW SPECIFICATIONS

(+) available in Canada only (f) available in US only *without bar and chain **clutch driven

Model	Engine Disp (cc)	Engine Disp. (cu. in.)	Starting System	Ignition System	Purge Bulb	Oiling System	Vibration Reduction	Available Bar Length (in.)	Fuel Cap. (fl. oz.)	Oil Cap. (fl. oz.)	Dry Weight* (lb.)
305s	30.5	1.86	i-30™	Digital	Yes	Automatic**	Yes	14	8.5	8.8	8.8
358Ts	35.8	2.19	Reduced Effort	Digital	Yes	Auto/Adjustable**	Yes	14, 16	11.2	8.2	8.0
402s	40.2	2.45	i-30™	Digital	Yes	Auto/Adjustable	Yes	18	13.9	9.5	10.1
492	50.2	3.06	Reduced Effort	Digital	No	Auto/Adjustable**	Yes	16 (+), 18, 20	16.6	9.5	10.6
591	59.8	3.65	Standard	Digital	No	Auto/Adjustable**	Yes	18 (+), 20	21.8	10.2	13.2
600sx	59.8	3.65	Standard	Digital	No	Auto/Adjustable**	Yes	20, 24, 27 (†)	21.8	10.2	13.7

TRIMMER SPECIFICATIONS

Model	Engine Disp (cc)	Overall Length (in.)	Fuel Cap. (fl. oz.)	Cutting Swath (in.)	Dry Weight (lb.)	Starting System	Vibration Reduction	Tool-Less Air Filter Access	Drive Shaft
T235	21.2	70.2	14.2	20	11.9	Standard	Yes	Yes	Solid Steel
T262	25.4	70.4	20.6	20	12.4	Standard	Yes	Yes	Hollow
T262X	25.4	70.5	20.6	20	13.7	Standard	Yes	Yes	Hollow
T302	30.5	70.4	24	20	13.7	Standard	Yes	Yes	4-Layer Cable
T302X	30.5	70.5	24	20	14.3	Standard	Yes	Yes	4-Layer Cable

BRUSHCUTTER SPECIFICATIONS

Model	Engine Disp (cc)	Overall Length (in.)	Fuel Cap. (fl. oz.)	Cutting Swath (in.)	Dry Weight (lb.)	Starting System	Vibration Reduction	Tool-Less Air Filter Access	Drive Shaft
C262	25.4	70.5	20.6	20	14.1	Standard	Yes	Yes	Solid Steel
C302	30.5	70.5	24	20	14.8	Standard	Yes	Yes	4-Layer Cable

EDGER SPECIFICATIONS

Model	Engine Disp (cc)	Overall Length (in.)	Fuel Cap. (fl. oz.)	Dry Weight (lb.)
LE235	21.2	69.7	14.2	13.2
LE262	25.4	69.7	20.6	14.3

BLOWER SPECIFICATIONS

*with blower pipe

Model	Engine Disp (cc)	Dry Weight* (lb.)	Fuel Cap. (fl. oz.)	dB(A)	FLARED PIPE		ROUND PIPE		TURBO PIPE	
					Air Volume (CFM)	Max Air Speed (MPH)	Air Volume (CFM)	Max Air Speed (MPH)	Air Volume (CFM)	Max Air Speed (CFM)
EB252	25.4	8.6	18.6	70	-	-	453	170	-	-
EB262	25.4	9.8	20.3	70	428	180	456	172	-	-
EB600RT	58.2	22.7	62.0	70	-	-	517	216	-	-
EB633RT	63.3	26.2	67.6	74	-	-	651	233	-	-
EB770/RT	63.3	24.5/24.3	68.3	74	-	-	756	234	-	-
EB802/RT	79.2	25.1/24.9	68.3	76	-	-	695	210	618	243
EB854/RT	79.7	28.0/27.6	68.7	77	-	-	735	191	660	213
EB910/RT	79.9	26.7/26.4	83.8	80	-	-	1,110	220	-	-

HEDGE TRIMMER SPECIFICATIONS

Model	Engine Disp (cc)	Blade Length (in.)	Shaft Length (in.)	Overall Length (in.)	Fuel Cap. (fl. oz.)	Dry Weight (lb.)	Vibration Reduction	Rotating Handle	Range	Exhaust Tube
DH232	21.2	22	-	41.9	12.5	11.0	Yes	Yes	-	Forward-facing
DH235	21.2	28	-	47	12.5	11.4	Yes	Yes	-	Forward-facing
HT232	21.2	28	-	41.5	12.5	10.2	Yes	-	-	Forward-facing
HT235	21.2	38	-	51.2	12.5	10.8	Yes	-	-	Forward-facing
FH235	21.2	21	42	79.4	14.2	12.5	Yes	-	-	-
AH262	25.4	21	59	96.1	20.6	14.3	Yes	-	135 Degrees - 10 Positions	-
AHS262	25.4	21	33	70.2	20.6	13.7	Yes	-	135 Degrees - 10 Positions	-

MULTI-TOOL SYSTEM SPECIFICATIONS

Model	Engine Disp (cc)	Dry Weight (lb.)	Fuel Capacity (fl. oz.)
M235	21.2	9.8	14.2
M262	25.4	10	20.6

POWERBROOM™ SPECIFICATIONS

Model	Engine Disp (cc)	Dry Weight (lb.)	Fuel Capacity (fl. oz.)
PS262	25.4	13.3	20.6

